


Datasheet for: 103016


Pressure switch mini design, Brass, G 1/8, Setting range 1-10 bar

Pressure switch mini design, Brass, 42 V, Ambient temperature -25 °C to 85 °C, G 1/8, Setting range 1 - 10 bar, NC contact . For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Type number	DS 215
Article number	103016
EAN/barcode	 4047322189880
Your price	19,81 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1


Productdata

Adjustment range max.	10.0 bar
Adjustment range min.	1.0 bar
Applications	Air, hydraulic oil, oil emulsions, water
Electrical connection	Tab connectors 2 x 6.3 x 0.8
Function	NC
Material	Brass
Max. ambient temperature	85 °C
Min. ambient temperature	-25 °C
Page No.	HK336
Switching frequency	200/min
Switching voltage	42 V
Thread	G 1/8
Type of construction	Spring-loaded diaphragm (NBR)

Variants

Article number	Function	Price
103016	NC	19,81 € / Stk
103015	NO	19,81 € / Stk

More Pictures



Schließler

Öffner