


Datasheet for: 106826


Pneumatically releasable check valve hose-thread, G 1/8 hose 6

Pneumatically releasable check valve »lineonline«, Hose - thread, G 1/8, for hose Ø 6 mm, Operating pressure max. 10 bar . For stopping and positioning the cylinder. If a signal is present at the pilot port, air can flow to and from the cylinder. If no pilot signal is present, the cylinder exhaust port is shut off by the stop valve. The cylinder is stopped.

Type number	495.018-6
Article number	106826
EAN/barcode	 4047322390231
Your price	26,93 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	58.5 mm
B	43.2 mm
Body	Technopolymer
Control air port	4 mm
Flow rate at 6.3 bar and Δp 1.0 bar	400 NI/min
For pipe Ø	6.0 mm
l	14.6 mm
Internal parts	Nickel-plated brass, brass, technopolymer, stainless steel
Max. operating pressure	10 bar
Max. temperature range	60 °C
Min. temperature range	-20 °C
Page No.	HK495
Pneumatic symbols	On housing
Sealant	NBR
Thread	G 1/8

Variants

Article number	Thread	For pipe Ø	Flow rate at 6.3 bar and Δp 1.0 bar	Price
106826	G 1/8	6.0 mm	400 NI/min	26,93 € / Stk
106827	G 1/8	8.0 mm	790 NI/min	27,57 € / Stk
106829	G 1/4	8.0 mm	790 NI/min	28,08 € / Stk
106830	G 3/8	8.0 mm	790 NI/min	29,12 € / Stk
106828	G 1/4	6.0 mm	400 NI/min	27,40 € / Stk

More Pictures

