


Datasheet for: 112934

Fitting elbow 97, IT/ET, Rp 2, R 2, black malleable cast iron


Fitting elbow 97, flat sealing, IT/ET, Rp 2, R 2, Operating temp. -20°C to 200°C, black malleable cast iron, Hot-dip galvanised . Maximum temperature and maximum operating pressure should not occur at the same time! Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines.

Type number	TFV 97-20
Article number	112934
EAN/barcode	 4047322396035
Your price	29,72 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	200 °C
Min. temperature range	-20 °C
Page No.	HK857
Standard	acc. ISO 7-1
thread	Hot dip galvanised
Surface	Rp 2
Thread 1	R 2
Thread 2	

Variants

<i>Article number</i>	<i>Thread 1</i>	<i>Thread 2</i>	<i>Price</i>
112934	Rp 2	R 2	29,72 € / Stk
112929	Rp 1/2	R 1/2	5,71 € / Stk
112932	Rp 1 1/4	R 1 1/4	15,10 € / Stk
112930	Rp 3/4	R 3/4	7,15 € / Stk
112933	Rp 1 1/2	R 1 1/2	21,69 € / Stk
112931	Rp 1	R 1	9,08 € / Stk