


## Datasheet for: 112950

**Bracket 120, 45°, IT/IT, Rp 2 1/2, black malleable cast iron**


Bracket 120, 45°, IT/IT, Rp 2 1/2, Operating temp. -20 °C to 300 °C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFW 120-212
Article number	112950
EAN/barcode	 4047322392020
Your price	27,30 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK857
Standard	acc. ISO 7-1
thread	Hot dip galvanised
Surface	Rp 2 1/2
Thread	

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
112950	Rp 2 1/2	27,30 € / Stk
112947	Rp 1 1/4	8,62 € / Stk
112949	Rp 2	12,94 € / Stk
112944	Rp 1/2	2,51 € / Stk
112946	Rp 1	4,48 € / Stk
112948	Rp 1 1/2	10,06 € / Stk
112945	Rp 3/4	2,87 € / Stk
112943	Rp 3/8	3,06 € / Stk
112951	Rp 3	28,75 € / Stk