


Datasheet for: 116328


Glycerine pressure gauge »pressure line« G 1/4, 0-10 bar/145 psi

Glycerine press. gauge »pressure line« Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range 0-10 bar/145 psi, Ø 63 . Low-priced series of high-quality, glycerine-filled pressure gauges with stainless steel housing for all applications involving measurements in areas with high dynamic pressure loads and vibration levels. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Type number	807-CDE
Article number	116328
EAN/barcode	 4047322177122
Your price	20,01 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	1.6
Connection	G 1/4
Connection position	rear, central
Diameter	63 mm
Front glass	Glass
Housing	Stainless steel
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Measuring element	Brass
Measuring range max. bar	10.0
Measuring range min. bar	0.0
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Movement	Brass
Page No.	WEB
Page No. AS	AS043

Scale graduation in the bar area
Version

0.2 bar

Bourdon-tube pressure gauge with glycerine filling

Variants

<i>Article number</i>	<i>Measuring range max. bar</i>	<i>Price</i>
116328	10.0	20,01 € / Stk
116325	2.5	20,01 € / Stk
116326	4.0	20,01 € / Stk
116327	6.0	20,01 € / Stk
116329	16.0	20,01 € / Stk
116330	25.0	20,01 € / Stk
116331	40.0	20,01 € / Stk
116332	60.0	20,01 € / Stk
116333	100.0	20,01 € / Stk
116334	160.0	20,01 € / Stk
116335	250.0	21,69 € / Stk
116336	400.0	21,69 € / Stk
116337	600.0	21,69 € / Stk