

Datasheet for: 116431


3/2-way blocking valve »G-mini«, Size 200, G 1/8

3/2-way blocking valve »G-mini« mounting bracket, Padlock and silencer, Manually actuated, Size 200, G 1/8, Input pressure 0-9 bar . Rotary switch can be turned 90°, lockable. The valve is used to switch off the air supply and is normally installed upstream of a pressure regulator, filter regulator or service unit. When the valve is closed, the residual air on the P2 side is discharged into the atmosphere through the relief port on the bottom.

Type number	GK 05
Article number	116431
EAN/barcode	 4047322309004
Your price	27,45 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	38.0 mm
B	89.0 mm
C	52.5 mm
D	36.5 mm
Flow rate	1750 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast aluminium
Max. ambient temperature	70 °C
Max. input pressure	9 bar
Max. medium temperature	70 °C
Min. input pressure	0.0 bar
Page No.	WEB
Sealant	NBR
Series	G-mini
Size	200
Thread	G 1/8
Twist knob	Plastics
Vent port	G 1/4

Variants

Article number	Thread	Price
116431	G 1/8	27,45 € / Stk
116432	G 1/4	27,45 € / Stk

More Pictures

