


Datasheet for: 106822


Pneumatically releasable check valve, thread - hose, G 1/8 hose 8

Pneumatically releasable check valve »lineonline«, Thread - hose, G 1/8, for hose Ø 8 mm, Operating pressure max. 10 bar . For stopping and positioning the cylinder. If a signal is present at the pilot port, air can flow to and from the cylinder. If no pilot signal is present, the cylinder exhaust port is shut off by the stop valve. The cylinder is stopped.

| | |
|----------------|--|
| Type number | 494.018-8 |
| Article number | 106822 |
| EAN/barcode |  4047322390170 |
| Your price | 27,57 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|---|--|
| A | 66.2 mm |
| B | 49.7 mm |
| Body | Technopolymer |
| Control air port | 4 mm |
| Flow rate at 6.3 bar and Δp 1.0 bar | 790 NI/min |
| For pipe Ø | 8.0 mm |
| I | 18.7 mm |
| Internal parts | Nickel-plated brass, brass, technopolymer, stainless steel |
| Max. operating pressure | 10 bar |
| Max. temperature range | 60 °C |
| Min. temperature range | -20 °C |
| Page No. | HK495 |
| Pneumatic symbols | On housing |
| Sealant | NBR |
| Thread | G 1/8 |

Variants

| Article number | Thread | For pipe Ø | Flow rate at 6.3 bar and Δp 1.0 bar | Price |
|----------------|--------|------------|---|---------------|
| 106822 | G 1/8 | 8.0 mm | 790 NI/min | 27,57 € / Stk |
| 106824 | G 1/4 | 8.0 mm | 790 NI/min | 28,08 € / Stk |
| 106821 | G 1/8 | 6.0 mm | 400 NI/min | 26,93 € / Stk |
| 106825 | G 3/8 | 8.0 mm | 790 NI/min | 29,12 € / Stk |
| 106823 | G 1/4 | 6.0 mm | 400 NI/min | 27,40 € / Stk |

More Pictures

