


Datasheet for: 113022


Angled distributor 221, IT/IT/IT, Rp 1 1/2

Angled distributor 221, IT/IT/IT, Rp 1 1/2, Operating temp. -20 °C to 300 °C, black malleable cast iron, Hot-dip galvanised . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFE 221-112
Article number	113022
EAN/barcode	 4047322395779
Your price	20,15 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK859
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	Rp 1 1/2

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
113022	Rp 1 1/2	20,15 € / Stk
113023	Rp 2	31,04 € / Stk
113021	Rp 1	7,85 € / Stk
113020	Rp 3/4	5,71 € / Stk
113019	Rp 1/2	3,55 € / Stk