


## Datasheet for: 103850


**Check valve, Lightweight construction, Stainless steel, G 3/8**

Check valve, Lightweight construction, Stainless steel 1.4301, Operating temperature -20 °C to 150 °C, G 3/8, PN max. 16 bar . Stainless steel check valve with full bore and very low opening pressure, no maintenance required. Applications: Compressed air, water, neutral gases, gaseous and liquid non-corrosive media, oils.

Type number	228.38-ES
Article number	103850
EAN/barcode	 4047322382496
Your price	30,29 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	20.0 mm
C	32.0 mm
Housing	Stainless steel 1.4301
L	56.0 mm
Max. operating pressure	16 bar
Max. operating temperature	150 °C
Min. opening pressure	0.03 bar
Min. operating temperature	-20 °C
Page No.	HK355
Sealant	FKM
Spring	Stainless steel 1.4301
Thread	G 3/8

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
103850	G 3/8	30,29 € / Stk
103852	G 3/4	41,29 € / Stk
103857	G 2 1/2	279,21 € / Stk
103851	G 1/2	31,03 € / Stk
103853	G 1	46,78 € / Stk
103854	G 1 1/4	65,22 € / Stk
103855	G 1 1/2	76,29 € / Stk
103858	G 3	391,98 € / Stk
103856	G 2	150,12 € / Stk
103849	G 1/4	30,29 € / Stk

## More Pictures

