


Datasheet for: 115956


3/2-way valve, Mechanically actuated, »M3«, Roller lever, G 1/8

3/2-way valve, Mechanically actuated, »M3«, Roller lever, NC, G 1/8, Operating pressure 0-10 bar, Temperature range -20°C to 70°C . 3/2-way valves - Mechanically operated -

| | |
|----------------|----------------------------------------------------------------------------------------------------|
| Type number | 511.2000 |
| Article number | 115956 |
| EAN/barcode |  4047322309219 |
| Your price | 37,93 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-------------------------|----------------------------------------------------------------|
| Connection | G 1/8 |
| Exhaust connection | G 1/8 |
| Flow rate | 450 l/min |
| Flow rate measurement | At P 1 = 8 bar, 2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Function | 3/2 NC |
| Max. operating pressure | 10 bar |
| Max. temperature range | 70 °C |
| Min. temperature range | -20 °C |
| Page No. | HK449 |
| Page No. AS | AS076 |
| Symbol | 3 |
| Valve body | Aluminium alloy |

Variants

| Article number | Connection | Exhaust connection | Flow rate | Price |
|----------------|------------|--------------------|-----------|---------------|
| 115956 | G 1/8 | G 1/8 | 450 l/min | 37,93 € / Stk |
| 115957 | G 1/4 | G 1/4 | 550 l/min | 37,93 € / Stk |

More Pictures

