


Datasheet for: 115986


3/2-way valve, Manually actuated, »M3«, Short lever, NC, G 1/8

3/2-way valve, Manually actuated, »M3«, Short lever, NC, monostable, G 1/8, Operating pressure - 10 bar, Temp. -20 °C to 70 °C . 3/2-way valves - Manually operated, for panel mounting -

| | |
|----------------|--|
| Type number | 515.2000 |
| Article number | 115986 |
| EAN/barcode |  4047322311335 |
| Your price | 37,93 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-------------------------|--|
| Connection | G 1/8 |
| Exhaust connection | G 1/8 |
| Flow rate | 450 l/min |
| Flow rate measurement | At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Function | 3/2 NC |
| Lever/switch colour | black |
| Max. operating pressure | 10 bar |
| Max. temperature range | 70 °C |
| Min. temperature range | -20 °C |
| Operation | Monostable |
| Page No. | HK453 |
| Page No. AS | AS078 |
| Symbol | 3 |
| Valve body | Aluminium alloy |

Variants

| Article number | Connection | Exhaust connection | Flow rate | Price |
|----------------|------------|--------------------|-----------|---------------|
| 115986 | G 1/8 | G 1/8 | 450 l/min | 37,93 € / Stk |
| 115987 | G 1/4 | G 1/4 | 550 l/min | 37,93 € / Stk |

More Pictures

