

## Datasheet for: 106992


**Throttle valve, Both sides throttling (»B«) G 1/2 IT, G 1/2**

Throttle valve, Both sides throttling (»B«) threaded connection, G 1/2 IT, G 1/2, PN max. 10 bar, Temperature °C to 70 °C . For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Type number	337.012-1/2
-------------	-------------

Article number	106992
----------------	--------

EAN/barcode	
-------------	--



4047322393904

Your price	30,65 € / Stk
------------	---------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Adjusting screw	Nickel-plated brass
B	81.0 mm
C	32.0 mm
Captive seals	Polyamide (glass fibre-reinforced)
Connection	G 1/2 female thread
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK503
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/2
a/f	26 mm

## Variants

Article number	Thread	Connection	a/f	Price
106992	G 1/2	G 1/2 female thread	26 mm	30,65 € / Stk
106989	G 1/8	G 1/8 female thread	14 mm	11,18 € / Stk
106990	G 1/4	G 1/4 female thread	17 mm	13,29 € / Stk
106991	G 3/8	G 3/8 female thread	20 mm	21,09 € / Stk
106988	M5	M5 female thread	8 mm	11,76 € / Stk

## More Pictures

