


Datasheet for: 115999


**3/2-way valve manual »M3« Push button, NC, monostable, G 1/4**

3/2-way valve manual »M3« Push button, NC, monost., Control panel integration, G 1/4, Operating pre. 0-10 bar, Temp. -20°C to 70°C . 3/2-way valves - Manually operated, for panel mounting -

Type number	515.4005
Article number	115999
EAN/barcode	 4047322311434
Your price	37,93 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1/4
Exhaust connection	G 1/4
Flow rate	550 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	3/2 NC
Lever/switch colour	green
Max. operating pressure	10 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Operation	Monostable
Page No.	HK454
Page No. AS	AS078
Symbol	1
Valve body	Aluminium alloy

## Variants

Article number	Connection	Exhaust connection	Flow rate	Lever/switch colour	Price
115999	G 1/4	G 1/4	550 l/min	green	37,93 € / Stk
115997	G 1/4	G 1/4	550 l/min	black	37,93 € / Stk
115994	G 1/8	G 1/8	450 l/min	black	37,93 € / Stk
115998	G 1/4	G 1/4	550 l/min	red	37,93 € / Stk
115996	G 1/8	G 1/8	450 l/min	green	37,93 € / Stk
115995	G 1/8	G 1/8	450 l/min	red	37,93 € / Stk

## More Pictures

