

Datasheet for: 138875


Ball valve fine adjustment, nickel-plated bright brass, Rp 1

Ball valve fine adjustment, Potable water suitable, nickel-plated bright brass, Temp. -15°C to 120°C, Rp 1, DN 25, PN max. 40 bar . Brass ball valves in the standard series with fine adjustment. Unlike our classic standard ball valves (open-close function), this model features a special stem technology that allows finely modulated opening and closing of the line. The flow rate can be regulated extremely precisely as a result. The cock is made of low-lead brass with a bare brass surface on the inside. It is thus safe to use with drinking water. This valve complies with the European standard EN 13828 and the working paper DVGW W 570.

Type number	335.106
-------------	---------

Article number	138875
----------------	--------

EAN/barcode



4047322527576

Your price	30,75 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	83.2 mm
B	79.7 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	25.0
DVGW approval	DIN EN 13828:2003-12, DVGW W 570
Housing	Nickel-plated brass (outside), brass with a bare metal surface (inside)
L	83.5 mm
Max. operating temperature	120 °C
Min. operating temperature	-15 °C
PN	40 bar
Page No.	HK291
Standard thread	Thread acc. to ISO 7/1
Stem seal	PTFE / NBR
Thread	Rp 1
Thread material	Brass with a bare metal surface
Wheel	Plastic

Variants

Article number	Thread	DN	PN	Price
138875	Rp 1	25.0	40 bar	30,75 € / Stk
138873	Rp 1/2	15.0	50 bar	20,00 € / Stk
138878	Rp 2	50.0	40 bar	100,80 € / Stk
138871	Rp 1/4	8.0	50 bar	18,91 € / Stk
138876	Rp 1 1/4	32.0	40 bar	50,78 € / Stk
138874	Rp 3/4	20.0	50 bar	23,25 € / Stk
138877	Rp 1 1/2	40.0	40 bar	66,90 € / Stk
138872	Rp 3/8	10.0	50 bar	18,91 € / Stk

More Pictures

