


Datasheet for: 135159


Push-in L-fitting, R 1/4 o., for hose exterior Ø 4, ES 1.4404

Push-in L-fitting, R 1/4 o., for hose exterior Ø 4 mm, Working pressure max. 20 bar, Stainless steel 1.4404 . For use in more aggressive environments and corrosive media.

Type number	852.014-4 ES
Article number	135159
EAN/barcode	 4047322493673
Your price	31,02 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	4 mm
L1	22.6 mm
L2	21.7 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	HK720
Standard thread	ISO 7-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	R 1/4
Working pressure pulsate	10.0 bar
a/f	14 mm

Variants

Article number	Thread	For tube O.D.	Price
135159	R 1/4	4 mm	31,02 € / Stk
135164	R 3/8	8 mm	44,81 € / Stk
135170	R 1/2	14 mm	87,80 € / Stk
135163	R 1/4	12 mm	66,51 € / Stk
135158	R 1/8	8 mm	27,01 € / Stk
135165	R 3/8	10 mm	55,10 € / Stk
135171	R 1/2	16 mm	92,33 € / Stk
135160	R 1/4	6 mm	25,39 € / Stk
135166	R 3/8	12 mm	74,48 € / Stk
135161	R 1/4	8 mm	30,74 € / Stk
135168	R 1/2	10 mm	65,09 € / Stk
135162	R 1/4	10 mm	39,40 € / Stk
135169	R 1/2	12 mm	75,99 € / Stk
135167	R 3/8	14 mm	83,26 € / Stk
135156	R 1/8	4 mm	23,53 € / Stk
135157	R 1/8	6 mm	23,53 € / Stk

More Pictures

