


Datasheet for: 112622

Through distributor, Input/Output G 3/4, Connection 1 x G 1/2


Through distributor, Input/Output G 3/4, Connection 1 x G 1/2, operat. pressure (air/water) max. 15 bar, ambient temp. 1 °C to 50 °C. Made of plastic PA6 GF 30. End and through distributor sockets made of high strength, glass fibre reinforced plastic (PA6 GF 30) with large range of applications. Optionally 1 or up to 3 connection options as well as 2 thread sizes for internal and external threads (cannot be combined). For vertical carrying of media. Universal distributor socket with up to 5 connection options. Suitable for vertical and/or horizontal carrying of media or the secure connection (avoidance of existing components) of pressure reducer or maintenance device, for example. All distributor sockets have a durable brass threaded insert, whose shape secures it against rotation and against axial shift due to its shape. Suitable for media compressed air (ambient temperature -10 °C to 50 °C) or water (ambient temperature 1 °C to 50 °C). Drilling diagram dimensions are identical for all distributor sockets, so a simpler and more flexible exchange between end, through and universal distributor sockets is ensured. Caution: Note that the distributor sockets should not be installed in danger zones. Danger zones are, for example, transport routes, escape routes, etc.

Type number	DVD34-1
Article number	112622
EAN/barcode	 4047322401609
Your price	38,40 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connecting thread	1 x G 1/2
Housing	Glass fibre-reinforced plastic PA6 GF 30
Inlet thread	G 3/4
Max. operating pressure	15 bar
Max. temperature range	50 °C
Max. tightening torque brass thread	12 Nm

Max. tightening torque 4 Nm
 mounting holes
 Min. temperature range 1 °C
 Page No. HK844
 Page No. TS TS010
 Through-hole thread G 3/4

Variants

<i>Article number</i>	<i>Inlet thread</i>	<i>Through-hole thread</i>	<i>Connecting thread</i>	<i>Price</i>
112622	G 3/4	G 3/4	1 x G 1/2	38,40 € / Stk
112621	G 1/2	G 1/2	3 x G 1/2	29,12 € / Stk
112623	G 3/4	G 3/4	2 x G 1/2	42,28 € / Stk
112619	G 1/2	G 1/2	1 x G 1/2	20,01 € / Stk
112624	G 3/4	G 3/4	3 x G 1/2	45,55 € / Stk
112620	G 1/2	G 1/2	2 x G 1/2	24,86 € / Stk