


Datasheet for: 114432


High-volume blow gun »Typhoon«, standard nozzle, Nipple I.D. 7.2

High-volume blow gun »Typhoon« standard nozzle, Aluminium, Operating temperature -10 °C bis 50 °C, PN max. 10 bar, Nipple I.D. 7.2 . Steplessly adjustable, lightweight and ergonomically optimised high-volume blow gun with exceptionally high blowing power. The »Typhoon« model, which achieves approximately three times the blowing power of conventional guns, rests comfortably and securely in the hand even when full pressure is applied. Extension tubes can be supplied for blowing out inaccessible points. In combination with safety nozzles, this blow gun meets a wide range of safety requirements.

Type number	29 K
Article number	114432
EAN/barcode	 4047322070201
Your price	31,25 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connecting thread	G 1/4
Hand lever	Die cast aluminium
Material	Aluminium
Max. operating pressure	10 bar
Nozzle	1/2" - 27 UNS
Nozzle type	Standard nozzle
Page No.	HK962
Page No. TS	TS024
Type of connection	Push-in plug for DN 7.2 coupling

Variants

<i>Article number</i>	<i>Type of connection</i>	<i>Price</i>
114432	Push-in plug for DN 7.2 coupling	31,25 € / Stk
114429	Stem, I.D. 6	31,25 € / Stk
114430	Stem, I.D. 9	31,25 € / Stk
114431	Stem, I.D. 13	31,25 € / Stk
118124	G 1/4 IT	29,91 € / Stk