


Datasheet for: 116046


3/2-way valve, Pneumatic, »3A«, bistable, M5

3/2-way valve, Pneumatic, »3A«, bistable, M5, Operating pressure 1.5 - 8 bar, Temperature range max. 70 °C . 3/2-way pilot valves - Pneumatic -

Type number	516.3000
Article number	116046
EAN/barcode	 4047322309479
Your price	31,31 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	M5
Control air port	G 1/8
Exhaust connection	M5
Flow rate	300 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	3/2
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Operation	Bistable
Page No.	HK463
Page No. AS	AS083
Size	100
Symbol	26
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
116046	M5	M5	300 l/min	100	31,31 € / Stk
116050	G 1/4	G 1/4	1300 l/min	300	39,82 € / Stk
116048	G 1/8	G 1/8	750 l/min	200	32,35 € / Stk
116047	G 1/8	G 1/8	500 l/min	100	31,31 € / Stk
116049	G 1/4	G 1/4	850 l/min	200	32,35 € / Stk
116051	G 3/8	G 3/8	1500 l/min	300	39,82 € / Stk

More Pictures

