

Datasheet for: 103145


Safety ball valve, lockable, without venting hole, Rp 1

Safety ball valve, lockable, without venting hole, nickel-plated brass, Operating temp. max. 170°C, Rp 1, DN 25, PN max. 65 bar . 2/2-way safety ball valves made of nickel-plated brass. The ball valve can be locked manually. Full bore, heavy-duty type.

Type number	320.06
Article number	103145
EAN/barcode	 4047322246880
Your price	38,90 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	120.0 mm
B	57.0 mm
Ball seal	PTFE
DN	25.0
Hand lever	Steel - PVC coated
L	90.5 mm
Material	Nickel-plated brass
Max. operating temperature	170 °C
Min. operating temperature	-40 °C
PN	65 bar
Page No.	HK280
Page No. SF	SF044
Standard thread	Rp thread acc. to EN 10226
Stem seal	PTFE
Thread	Rp 1
Thread material	Nickel-plated brass

Variants

Article number	Thread	DN	PN	Price
103145	Rp 1	25.0	65 bar	38,90 € / Stk
103142	Rp 3/8	10.0	65 bar	14,58 € / Stk
103141	Rp 1/4	8.0	65 bar	14,58 € / Stk
103144	Rp 3/4	20.0	65 bar	25,90 € / Stk
103148	Rp 2	50.0	40 bar	102,45 € / Stk
103146	Rp 1 1/4	32.0	40 bar	51,68 € / Stk
103143	Rp 1/2	15.0	65 bar	16,74 € / Stk
103147	Rp 1 1/2	40.0	40 bar	70,69 € / Stk

More Pictures

