

## Datasheet for: 103880


**Check valve, reduced passage, G 2, 20 mbar**

Check valve, reduced passage, Operating temperature -10 °C to 100 °C, G 2, PN max. 16 bar, Opening pressure 20 mbar . Compact, low-price non-return valves with very low opening pressure.

Type number	227.46
-------------	--------

Article number	103880
----------------	--------

EAN/barcode	 4047322047890
-------------	--



Your price	31,46 € / Stk
------------	---------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Housing	Brass
Length	78.0 mm
Max. operating pressure	16 bar
Max. operating temperature	100 °C
Min. opening pressure	0.02 bar
Min. operating temperature	-10 °C
Page No.	HK357
Sealant	NBR
Spool	Polyether imide (PEI)
Spring	Stainless steel
Thread	G 2
a/f	67 mm

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Max. operating pressure</i>	<i>a/f</i>	<i>Price</i>
103880	G 2	16 bar	67 mm	31,46 € / Stk
103875	G 1/2	40 bar	25 mm	5,29 € / Stk
103876	G 3/4	40 bar	31 mm	6,81 € / Stk
103877	G 1	25 bar	38 mm	9,74 € / Stk
103878	G 1 1/4	25 bar	48 mm	14,22 € / Stk
103879	G 1 1/2	16 bar	54 mm	20,62 € / Stk