


Datasheet for: 116519


2/2-way solenoid valve »2W« NC, directly operated, 230 V, 50 Hz

2/2-way solenoid valve »2W«, Brass, NC, directly operated, 230 V, 50 Hz, Medium temp. max. 80 °C / 90 °C, G 1/8, PN - 10 bar . Standard series available in two different versions: -Directly operated -Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media. Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Type number	MV 1501
Article number	116519
EAN/barcode	 4047322324441
Your price	39,36 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
B	40.0 mm
C	70.7 mm
DN	3
Housing	Brass
Internal parts	Stainless steel
Max. operating pressure	10 bar
Page No.	HK324
Page No. AS	AS046
Protection IP	IP 65
Sealant	FPM
Standard thread	G thread acc. to DIN EN ISO 228-1
Thread	G 1/8
Type	1
Valve seat	Brass

Variants

<i>Article number</i>	<i>Thread</i>	<i>DN</i>	<i>Price</i>
116519	G 1/8	3	39,36 € / Stk
116525	G 1/2	5	58,27 € / Stk
116521	G 1/4	3	39,36 € / Stk
116523	G 3/8	5	58,27 € / Stk

More Pictures

