


## Datasheet for: 116529


**2/2-way solenoid valve »2W« NC, directly operated, 24 V DC, G 1/4**

2/2-way solenoid valve »2W«, Brass, NC, directly operated, 24 V DC, Medium temperature max. 80 °C / 90 °C, G 1/4, PN - 10 bar . Standard series available in two different versions: -Directly operated -Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media. Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

|                |                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------|
| Type number    | MV 1512                                                                                            |
| Article number | 116529                                                                                             |
| EAN/barcode    | <br>4047322324625 |
| Your price     | 39,36 € / Stk                                                                                      |

**Minimum order quantity**

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

**Productdata**

|                         |                                   |
|-------------------------|-----------------------------------|
| A                       | 70.0 mm                           |
| B                       | 40.0 mm                           |
| C                       | 70.7 mm                           |
| DN                      | 3                                 |
| Housing                 | Brass                             |
| Internal parts          | Stainless steel                   |
| Max. operating pressure | 10 bar                            |
| Page No.                | HK324                             |
| Page No. AS             | AS046                             |
| Protection IP           | IP 65                             |
| Sealant                 | FPM                               |
| Standard thread         | G thread acc. to DIN EN ISO 228-1 |
| Thread                  | G 1/4                             |
| Type                    | 1                                 |
| Valve seat              | Brass                             |

## Variants

| Article number | Thread | DN | Price         |
|----------------|--------|----|---------------|
| 116529         | G 1/4  | 3  | 39,36 € / Stk |
| 116527         | G 1/8  | 3  | 39,36 € / Stk |
| 116531         | G 3/8  | 5  | 58,27 € / Stk |
| 116533         | G 1/2  | 5  | 58,27 € / Stk |

## More Pictures

