


Datasheet for: 107057


Pneumatically piloted stop valve, G 1/8, G 1/8 i., M5

Pneumatically piloted stop valve, G 1/8, G 1/8 i., M5, Working pressure 0.3 - 10 bar, Temperature max. 60 °C . For stopping and positioning the cylinder movement: If a control signal is present at port 3 (see drawing), air can flow to and from the cylinder. If no control signal is present, the cylinder exhaust air is shut off by the unidirectional valve. The cylinder is stopped. Releasable unidirectional valves are screwed directly onto the cylinder instead of the normal pipe connections. Note: Pilot pressure is depending on operating pressure.

Type number	63.018-18
Article number	107057
EAN/barcode	 4047322107037
Your price	39,37 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

B	38.0 mm
C	21.5 mm
Material	Nickel-plated brass
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Max. operating pressure	10 bar
Max. pilot pressure	2.5 bar
Min. operating pressure	0.3 bar
Min. pilot pressure	0.5 bar
Mounting position	Any, ring piece must be pos. before tightening the valve
Page No.	HK507
Port 1	G 1/8
Port 2	G 1/8
Port 3	M5
Sealant	NBR

Variants

Article number	Port 1	Port 2	Port 3	Price
107057	G 1/8	G 1/8	M5	39,37 € / Stk
107058	G 1/4	G 1/4	G 1/8	45,66 € / Stk
107059	G 3/8	G 3/8	G 1/8	56,02 € / Stk
107060	G 1/2	G 1/2	G 1/8	86,54 € / Stk

More Pictures

