


Datasheet for: 107794


GEKA threaded piece, rigid, Safety design, bright brass, G 3/4 o.

GEKA threaded piece, rigid, Safety design, bright brass, G 3/4 o., Operating pressure max. 40 bar, Med./ambient temp -10°C to 90°C . Claw couplings (claw distance: 40 mm) made of brass for water, industrial, mortar, suction and discharge hoses. Suitable for a wide range of applications, e.g. industrial plant engineering, civil and structural engineering, environmental engineering, manual trades, domestic water engineering, horticulture and landscaping, agriculture and forestry, etc. Available in a rigid or 360° swivelling version. The two systems can also be easily coupled to one another!

Type number	K 411 A
Article number	107794
EAN/barcode	 4047322387880
Your price	39,37 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 3/4 ET
Max. ambient temperature	90 °C
Max. medium temperature	90 °C
Max. operating pressure	40 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK608
Sealant	NBR

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107794	G 3/4 ET	39,37 € / Stk
107795	G 1 ET	42,28 € / Stk