

## Datasheet for: 135251


**Straight push-in connector, reducing, for hose exterior Ø 10/8 mm**

Straight push-in connector, reducing, for hose exterior Ø 10/8 mm, Working pressure max. 20 bar, Stainless steel 1.4404 . For use in more aggressive environments and corrosive media.

Type number	847.1008 ES
-------------	-------------

Article number	135251
----------------	--------

EAN/barcode



4047322494564

Your price	39,45 € / Stk
------------	---------------

**Minimum order quantity**

Price Unit	1
------------	---

Quantity Unit	Stk
---------------	-----

Packaging Unit	1
----------------	---

Content	1 Stk
---------	-------

Minimum order quantity	1
------------------------	---

**Productdata**

For tube O.D.	10/8 mm
L1	36.0 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	HK722
Suitable pipe materials	PVDF, PTFE, PA, PU
Working pressure pulsate	10.0 bar

## Variants

<i>Article number</i>	<i>For tube O.D.</i>	<i>Price</i>
135251	10/8 mm	39,45 € / Stk
135253	14/12 mm	65,86 € / Stk
135252	12/10 mm	52,82 € / Stk
135254	16/12 mm	75,32 € / Stk
135249	6/4 mm	24,13 € / Stk
135250	8/6 mm	24,94 € / Stk

## More Pictures

