


Datasheet for: 115963



5/2-way valve, Mechanically »M5« Roller lever, Free return, G 1/4

5/2-way valve, Mechanically actuated, »M5«, Roller lever, Free return, G 1/4, Operating pressure - 10 bar, Temp. -20 °C to 70 °C . 5/2-way valves - Mechanically operated -

Type number	511.3101
Article number	115963
EAN/barcode	 4047322309325
Your price	39,46 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
Exhaust connection	G 1/8
Flow rate	550 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Max. operating pressure	10 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Page No.	HK451
Page No. AS	AS077
Symbol	2
Valve body	Aluminium alloy

Variants

<i>Article number</i>	<i>Connection</i>	<i>Flow rate</i>	<i>Price</i>
115963	G 1/4	550 l/min	39,46 € / Stk
115962	G 1/8	450 l/min	39,46 € / Stk

More Pictures

