


Datasheet for: 107477

**Quick-connect coupling I.D. 12, Garage coupling, G 1/2 ET**


Quick-connect coupling I.D. 12, Garage coupling, Bright brass, G 1/2 ET, Pressure max. 16 bar, Medium/ambient temp. -10°C to 50°C . One-hand quick disconnect couplings, one side sealing, for high flow rates. With rubber ring to protect against wear. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Machine and plant engineering, manufacturing industry, workshops.

Type number	243.60
Article number	107477
EAN/barcode	 4047322060349
Your price	32,19 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1/2 ET
DN	12
Flow rate	4150 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Length	82.0 mm
Material	Brass with a bare metal surface
Max. ambient temperature	50 °C
Max. medium temperature	50 °C
Max. operating pressure	16 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK554
Page No. SK	SK036
Sealant	NBR
Spring	Stainless steel
a/f	30 mm

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107477	G 1/2 ET	32,19 € / Stk
107478	G 3/4 ET	32,19 € / Stk

## More Pictures

