


## Datasheet for: 107030


**3/2-way toggle lever valve, Hose side, Quick connector, G 1/4**

3/2-way toggle lever valve, Hose side, Quick connector Hose 10/8, G 1/4, PN max. 8 bar, Temp. °C to 70 °C, nickel-plated brass. Manually operated toggle valves, 2/2 and 3/2-way types. For all applications where compressed air must be switched on or off quickly and easily or a cylinder operated manually. Designed as a banjo-type valve with a hollow bolt and ring piece. Suitable for screwing directly into the equipment or for panel mounting. Compact type of construction, also ideal where space is restricted.

|                |  |
|----------------|--|
| Type number    | 361.014-10   |
| Article number | 107030   |
| EAN/barcode    | <br>4047322181266 |
| Your price     | 32,27 € / Stk  |

**Minimum order quantity**

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

**Productdata**

|                           |                                      |
|---------------------------|--------------------------------------|
| B                         | 60.0 mm                              |
| C                         | 28.5 mm                              |
| Captive seals             | Polyamide (glass fibre-reinforced)   |
| For hose                  | 10 / 8 mm                            |
| Hollow bolt               | Nickel-plated brass                  |
| Internal parts            | Brass with a bare metal surface      |
| Max. operating pressure   | 8 bar                                |
| Max. temperature range    | 70 °C                                |
| Page No.                  | HK505                                |
| Pivoting arm              | Nickel-plated brass                  |
| Sealant                   | NBR                                  |
| Thread                    | G 1/4                                |
| Thread for panel mounting | M12x0.75 (max. plate thickness 4 mm) |
| Toggle                    | Nickel-plated brass                  |
| Version                   | 3/2-way                              |
| a/f                       | 17 mm                                |

## Variants

| Article number | Thread | For hose               | a/f   | Price         |
|----------------|--------|------------------------|-------|---------------|
| 107030         | G 1/4  | 10 / 8 mm              | 17 mm | 32,27 € / Stk |
| 107024         | G 1/8  | 5 / 3 mm               | 14 mm | 27,14 € / Stk |
| 107023         | G 1/8  | G 1/8 female thread mm | 14 mm | 28,77 € / Stk |
| 107025         | G 1/8  | 6 / 4 mm               | 14 mm | 28,77 € / Stk |
| 107026         | G 1/8  | 8 / 6 mm               | 14 mm | 28,77 € / Stk |
| 107027         | G 1/4  | G 1/4 female thread mm | 17 mm | 32,27 € / Stk |
| 107028         | G 1/4  | 6 / 4 mm               | 17 mm | 32,27 € / Stk |
| 107029         | G 1/4  | 8 / 6 mm               | 17 mm | 32,27 € / Stk |

## More Pictures

