


Datasheet for: 100286


Ball valve 3/2-way »FUTURA«, lockable, Size 2, G 1/2

Ball valve 3/2-way »FUTURA«, lockable, Size 2, G 1/2, Exhaust G 1/2, Input pressure max. 16 bar, Temperature -10 °C to 50 °C . Lockable ball valve, 3/2-way type including silencer, mechanically operated. Rotary switch can be turned 90°, with indication of positions: Horizontal: Input closed - outlet exhausted Vertical: Flow open - exhaust closed Exhaust air can be collected.

Type number	FU 982
Article number	100286
EAN/barcode	 4047322214841
Your price	47,76 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	63.0 mm
B	127.0 mm
C	70.5 mm
Connecting thread	Material: Die-cast zinc
Exhaust air	G 1/2
Flow rate	14000 l/min
Flow rate measurement	At P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Housing	PA66 GF60
Max. input pressure	16 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. temperature range	-10 °C
Page No.	HK054
Page No. SF	SF018
Series	FUTURA
Size	2
Thread	G 1/2

Variants

Article number	Thread	Exhaust air	Flow rate	Size	Price
100286	G 1/2	G 1/2	14000 l/min	2	47,76 € / Stk
100283	G 1/4	G 1/4	1900 l/min	1	32,41 € / Stk
100284	G 3/8	G 1/4	1900 l/min	1	32,41 € / Stk
100285	G 3/8	G 1/2	14000 l/min	2	47,76 € / Stk
100288	G 1	G 3/4	25000 l/min	4	107,74 € / Stk
100287	G 3/4	G 3/4	25000 l/min	4	107,74 € / Stk

More Pictures

