


Datasheet for: 103229


Safety ball valve with spring reset, nickel-plated brass, Rp 1/2

Safety ball valve with spring reset, nickel-plated brass, Operating temperature -40 °C to 170 °C, Rp 1/2, DN 15, PN max. 65 bar . 2/2-way safety ball valves, two parts, made of nickel-plated brass with spring return. The ball valve is closed in the normal position and opens against spring force. High safety standard because the valve is automatically closed if the handle is not operated; inadvertent opening is prevented.

Type number	KHF-12
Article number	103229
EAN/barcode	 4047322370042
Your price	41,09 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	100.0 mm
B	43.0 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	15.0
Hand lever	Steel - PVC coated
Housing	Nickel-plated brass
L	75.0 mm
Max. operating temperature	170 °C
Min. operating temperature	-40 °C
PN	65 bar
Page No.	HK280
Page No. SF	SF046
Spring	Stainless steel 1.4301
Standard thread	Rp thread acc. to ISO 7-1
Stem seal	FKM
Thread	Rp 1/2
Thread material	Nickel-plated brass

Variants

Article number	Thread	DN	PN	Price
103229	Rp 1/2	15.0	65 bar	41,09 € / Stk
103234	Rp 2	50.0	40 bar	244,51 € / Stk
103230	Rp 3/4	20.0	65 bar	53,72 € / Stk
103228	Rp 3/8	10.0	65 bar	41,09 € / Stk
103231	Rp 1	25.0	65 bar	79,61 € / Stk
103233	Rp 1 1/2	40.0	40 bar	160,63 € / Stk
103232	Rp 1 1/4	32.0	40 bar	118,78 € / Stk
103227	Rp 1/4	8.0	65 bar	41,09 € / Stk

More Pictures

