


Datasheet for: 106401


3/2-way mini valve manual, Rotating knob, NC, monostable, 4mm side

3/2-way miniature valve manual, Rotating knob, NC, monostable, 4 mm side, Operating pre. 0.5-10 bar, Operating temp. -10°C to 60°C . Monostable (non-latching) and bistable (latching) versions available.

Type number	512.203
Article number	106401
EAN/barcode	 4047322096300
Your price	41,17 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	Plug-in connector Ø 4 mm on side
Flow rate at 6 bar and Δp 0.5 bar	35 NI/min
Function	3/2 NC
Max. operating pressure	10 bar
Max. operating temperature	60 °C
Min. operating pressure	0.5 bar
Min. operating temperature	-10 °C
Nominal Ø	2.5 mm
Operating pressure at 6 bar	8 N
Operation	Monostable
Page No.	HK452
Pushbutton	Nickel-plated brass
Sealant	NBR
Spring	Stainless steel
Valve body	Aluminium

Variants

Article number	Connection	Operation	Price
106401	Plug-in connector Ø 4 mm on side	Monostable	41,17 € / Stk
106402	M5 female thread on side	Monostable	40,58 € / Stk
106403	Plug-in connector Ø 4 mm on side	Bistable	40,93 € / Stk
106404	M5 female thread on side	Bistable	40,58 € / Stk

More Pictures

