


Datasheet for: 151730


Stainless steel safety ball valve, lockable, Venting hole, G 1/4

Stainless steel safety ball valve, lockable, Venting hole M5, Operating temp. -20 °C to 160 °C, G 1/4, DN 11.5, PN max. 17 bar . Stainless steel safety ball valves. Specially designed for pneumatic applications. The ball valve can be locked manually and has a relief port.

Type number	3396.02
Article number	151730
EAN/barcode	 4047322594950
Your price	48,10 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	103.9 mm
B	50.0 mm
Ball	Stainless steel 1.4408
Ball seal	PTFE
DN	11.5
Hand lever	Stainless steel 1.4301, PVC coated
Housing	Stainless steel 1.4408
L	54.4 mm
Max. operating pressure	17 bar
Max. operating temperature	160 °C
Min. operating temperature	-20 °C
Note	The images maybe different from the original part
Page No.	HK282
Relief port	M5
Standard thread	G thread acc. to DIN EN ISO 228-1
Stem seal	PTFE
Thread	G 1/4

Variants

Article number	Thread	DN	Price
151730	G 1/4	11.5	48,10 € / Stk
151732	G 1/2	15.0	51,09 € / Stk
151733	G 3/4	20.0	68,55 € / Stk
151734	G 1	25.0	90,22 € / Stk
151731	G 3/8	12.5	49,82 € / Stk

More Pictures

