

Datasheet for: 133873


**Pressure gauge in-line filter, G 1/4 IT, G 1/4 ET, 200  $\mu\text{m}$** 

Pressure gauge in-line filter, G 1/4 IT, G 1/4 ET, 200  $\mu\text{m}$ , stainless steel 1.4571, max. 100 bar, Temp. -25 °C to 200 °C . Pressure gauge in-line filters are installed on pressure gauges in dirt-sensitive hydraulic / pneumatic system circuits in order to filter out solids from gaseous and liquid media (floating body retention). Stoppage of small pressure inlet channels and capillary throttles is prevented by their use. Furthermore particles do not jam in dirt-sensitive media chambers and the resulting appearances of a jam are avoided. Preliminary filters act as throttles and dampers with pressure shocks and pressure surges.

Type number	9030
Article number	133873
EAN/barcode	 4047322482295
Your price	44,13 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Filter rating	200.0 $\mu\text{m}$
Length	32.0 mm
Material	Stainless steel 1.4571
Max. temperature range	200 °C
Min. temperature range	-25 °C
Page No.	HK230
Pressure range	Max. 100 bar
Thread 1	G 1/4 ET
Thread 2	G 1/4 IT
a/f	17 mm

## Variants

<i>Article number</i>	<i>Thread 1</i>	<i>Thread 2</i>	<i>a/f</i>	<i>Price</i>
133873	G 1/4 ET	G 1/4 IT	17 mm	44,13 € / Stk
143860	G 1/2 ET	G 1/2 IT	27 mm	49,57 € / Stk