


Datasheet for: 116068


5/3-way valve, Pneumatic, »4A«, Centre closed, G 1/8

 5/3-way valve, Pneumatic, »4A«, Centre closed, G 1/8,
 Operating pressure 1.5 - 8 bar, Temperature range max. 70
 °C . 5/3-way pilot valves - Pneumatic -

Type number	516.6002
Article number	116068
EAN/barcode	 4047322309714
Your price	48,19 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Control air port	G 1/8
Exhaust connection	G 1/8
Flow rate	550 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/3
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Operation	Mid-position closed
Page No.	HK465
Page No. AS	AS085
Size	200
Symbol	29
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
116068	G 1/8	G 1/8	550 l/min	200	48,19 € / Stk
116066	M5	M5	250 l/min	100	45,96 € / Stk
116067	G 1/8	G 1/8	400 l/min	100	45,96 € / Stk
116070	G 1/4	G 1/4	950 l/min	300	52,14 € / Stk
116072	G 1/2	G 1/2	1600 l/min	400	115,11 € / Stk
116069	G 1/4	G 1/8	550 l/min	200	48,19 € / Stk
116071	G 3/8	G 1/4	950 l/min	300	52,14 € / Stk

More Pictures

