


Datasheet for: 116063


5/2-way valve, Pneumatic, »4A«, bistable, G 1/4

5/2-way valve, Pneumatic, »4A«, bistable, G 1/4, Operating pressure 1.5 - 8 bar, Temperature range max. 70 °C . 5/2-way pilot valves - Pneumatic -

Type number	516.5004
Article number	116063
EAN/barcode	 4047322309660
Your price	44,46 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
Control air port	G 1/8
Exhaust connection	G 1/4
Flow rate	1300 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Operation	Bistable
Page No.	HK464
Page No. AS	AS084
Size	300
Symbol	28
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
116063	G 1/4	G 1/4	1300 l/min	300	44,46 € / Stk
116059	M5	M5	300 l/min	100	31,78 € / Stk
116064	G 3/8	G 1/4	1500 l/min	300	44,46 € / Stk
116061	G 1/8	G 1/8	750 l/min	200	34,33 € / Stk
116065	G 1/2	G 1/2	2000 l/min	400	79,73 € / Stk
116060	G 1/8	G 1/8	500 l/min	100	31,78 € / Stk
116062	G 1/4	G 1/8	850 l/min	200	34,33 € / Stk

More Pictures

