

Datasheet for: 108136


Kamlok quick-connect plug, ET, F type, 1.4401, R 2 1/2

Kamlok quick-connect plug with exterior thread, F type, Stainless steel 1.4401, R 2 1/2, Plug Ø 76 mm, Pressure max. 16 bar . High-quality, robust, universal coupling system with a safety clamp for quick and easy connection of two hoses or for joining one hose to a machine connection. A male part and a female part are joined together by shifting the handles. There is no need to turn the hose! Kamlok stainless steel couplings are designed for use with corrosive media in the chemical and petrochemical industries, steelmaking, shipbuilding, agriculture, etc. All female threaded couplings and connectors are with female thread sealing ring made of PTFE.

Type number	1116.212-ES
-------------	-------------

Article number	108136
----------------	--------

EAN/barcode	 4047322404761
-------------	--

Your price	44,59 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

L	89.5 mm
Max. operating pressure	16 bar
Max. temperature range	95 °C
Min. temperature range	-20 °C
Page No.	HK624
Plug Ø	76 mm
Sealant	NBR, resistant to oils and benzine
Thread	R 2 1/2

Variants

Article number	Thread	Plug Ø	Price
108136	R 2 1/2	76 mm	44,59 € / Stk
108137	R 3	92 mm	57,43 € / Stk
108138	R 4	120 mm	90,29 € / Stk
108134	R 1 1/2	53 mm	19,26 € / Stk
108135	R 2	63 mm	27,76 € / Stk
108133	R 1 1/4	46 mm	14,68 € / Stk
108132	R 1	37 mm	10,56 € / Stk
108131	R 3/4	32 mm	7,39 € / Stk

More Pictures

