

Datasheet for: 115992



5/2-way valve, Manually actuated, »M5«, Toggle lever, G 1/8

5/2-way valve, Manually actuated, »M5«, Toggle lever, bistable, G 1/8, Operating pressure - 10 bar, Temp. range -20 °C to 70 °C . 5/2-way valves - Manually operated, for panel mounting -

Type number 515.3100

Article number 115992

EAN/barcode



4047322311649

Your price 41,67 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Exhaust connection	G 1/8
Flow rate	450 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Lever/switch colour	black
Max. operating pressure	10 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Operation	Bistable
Page No.	HK457
Page No. AS	AS080
Symbol	4
Valve body	Aluminium alloy

Variants

<i>Article number</i>	<i>Connection</i>	<i>Flow rate</i>	<i>Price</i>
115992	G 1/8	450 l/min	41,67 € / Stk
115993	G 1/4	550 l/min	68,32 € / Stk

More Pictures

