


Datasheet for: 116025


5/2-way valve manual »M5« Rotating handle, monostable, G 1/8

5/2-way valve manual »M5« Rotating handle, monost., Control panel integration, G 1/8, Operating pre. 0-10 bar, Temp. -20°C to 70°C . 5/2-way valves - Manually operated, for panel mounting -

Type number	515.6101
Article number	116025
EAN/barcode	 4047322311830
Your price	41,67 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Exhaust connection	G 1/8
Flow rate	450 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Lever/switch colour	red
Max. operating pressure	10 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Operation	Monostable
Page No.	HK457
Page No. AS	AS080
Symbol	3
Valve body	Aluminium alloy

Variants

Article number	Connection	Flow rate	Lever/switch colour	Price
116025	G 1/8	450 l/min	red	41,67 € / Stk
116029	G 1/4	550 l/min	green	56,11 € / Stk
116027	G 1/4	550 l/min	black	56,11 € / Stk
116028	G 1/4	550 l/min	red	56,11 € / Stk
116024	G 1/8	450 l/min	black	41,67 € / Stk
116026	G 1/8	450 l/min	green	41,67 € / Stk

More Pictures

