

Datasheet for: 108162


Kamlok cap plug, DP type, St. steel 1.4401, Size 4, Plug Ø 120

Kamlok cap plug, DP type, Stainless steel 1.4401, Size 4, Plug Ø 120 mm, Operating pressure max. 16 bar, Temp. -20 °C to 95 °C . High-quality, robust, universal coupling system with a safety clamp for quick and easy connection of two hoses or for joining one hose to a machine connection. A male part and a female part are joined together by shifting the handles. There is no need to turn the hose! Kamlok stainless steel couplings are designed for use with corrosive media in the chemical and petrochemical industries, steelmaking, shipbuilding, agriculture, etc. All female threaded couplings and connectors are with female thread sealing ring made of PTFE.

Type number	1119.40-ES
-------------	------------

Article number	108162
----------------	--------

EAN/barcode	
-------------	--



4047322405034

Your price	48,81 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	119.5 mm
C	58.0 mm
Max. operating pressure	16 bar
Max. temperature range	95 °C
Min. temperature range	-20 °C
Page No.	HK624
Plug Ø	120 mm
Sealant	NBR, resistant to oils and benzine
Size	4

Variants

Article number	Size	Plug Ø	Price
108162	4	120 mm	48,81 € / Stk
108159	2	63 mm	18,62 € / Stk
108156	1	37 mm	6,33 € / Stk
108155	3/4	32 mm	4,95 € / Stk
108158	1 1/2	53 mm	12,61 € / Stk
108160	2 1/2	76 mm	25,38 € / Stk
108157	1 1/4	46 mm	8,65 € / Stk
108161	3	92 mm	34,83 € / Stk

More Pictures

