


## Datasheet for: 108104

### Kamlok quick-connect socket, C type, 1.4401, Hose I.D. 63



Kamlok quick-connect socket, Hose supports, C type, Stainless steel 1.4401, Hose I.D. 63, for plug Ø 76.5 mm, Pressure max. 16 bar . High-quality, robust, universal coupling system with a safety clamp for quick and easy connection of two hoses or for joining one hose to a machine connection. A male part and a female part are joined together by shifting the handles. There is no need to turn the hose! Kamlok stainless steel couplings are designed for use with corrosive media in the chemical and petrochemical industries, steelmaking, shipbuilding, agriculture, etc. All female threaded couplings and connectors are with female thread sealing ring made of PTFE.

Type number	1112.212-ES
Article number	108104
EAN/barcode	 4047322404365
Your price	49,18 € / Stk

### Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

### Productdata

A	109.5 mm
C	131.5 mm
For hose I.D.	63
For plug Ø	76.5 mm
Max. operating pressure	16 bar
Max. temperature range	95 °C
Min. temperature range	-20 °C
Page No.	HK623
Sealant	NBR, resistant to oils and benzine

## Variants

Article number	For hose I.D.	For plug Ø	Price
108104	63	76.5 mm	49,18 € / Stk
108099	19	32.0 mm	15,93 € / Stk
108103	50	64.0 mm	38,47 € / Stk
108101	32	46.0 mm	27,97 € / Stk
108102	38	54.0 mm	28,77 € / Stk
108105	75	92.0 mm	71,09 € / Stk
108100	25	37.0 mm	17,47 € / Stk
108106	100	120.0 mm	110,09 € / Stk

## More Pictures

