


Datasheet for: 103291


Ball valve heavy duty design, Butterfly handle, IT/IT, G 1

Ball valve heavy duty design, Butterfly handle, IT/IT, nickel-plated brass, Operating temp. -20°C to 130°C, G 1, PN max. 80 bar . Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Type number	3340.06
Article number	103291
EAN/barcode	 4047322216333
Your price	49,28 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
B	73.0 mm
Ball	Chrome-plated brass
Ball seal	PTFE
Butterfly handle	Aluminium, painted black
DN	25.0
E	13.5 mm
F	13.5 mm
Housing	Nickel-plated brass
L	76.0 mm
Max. operating temperature	130 °C
Min. operating temperature	-20 °C
PN	80 bar
Page No.	HK274
Standard thread	G thread acc. to DIN EN ISO 228-1
Stem seal	PTFE
Thread	G 1
Thread material	Brass with a bare metal surface
a/f	39 mm

Variants

Article number	Thread	DN	a/f	Price
103291	G 1	25.0	39 mm	49,28 € / Stk
103290	G 3/4	20.0	32 mm	31,34 € / Stk
103289	G 1/2	15.0	26 mm	20,51 € / Stk
103288	G 3/8	10.0	21 mm	16,32 € / Stk
103287	G 1/4	8.0	18 mm	13,63 € / Stk

More Pictures

