


Datasheet for: 103296


Ball valve heavy duty design, Butterfly handle, IT/ET, G/R 1

Ball valve heavy duty design, Butterfly handle, IT/ET, nickel-plated brass, Operating temp. -20°C to 130°C, G/R 1, PN max. 80 bar . Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Type number	3340.16
Article number	103296
EAN/barcode	 4047322216388
Your price	49,28 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
B	70.5 mm
Ball	Chrome-plated brass
Ball seal	PTFE
Butterfly handle	Aluminium, painted black
DN	25.0
E	19.0 mm
F	14.5 mm
Housing	Nickel-plated brass
L	88.4 mm
Max. operating temperature	130 °C
Min. operating temperature	-20 °C
PN	80 bar
Page No.	HK274
Standard thread	G thread DIN EN ISO 228-1, R thread DIN EN 10226 (ISO 7-1)
Stem seal	PTFE
Thread	G/R 1
Thread material	Brass with a bare metal surface
a/f 1	40.0 mm
a/f 2	39.0 mm

Variants

Article number	Thread	DN	a/f 1	a/f 2	Price
103296	G/R 1	25.0	40.0 mm	39.0 mm	49,28 € / Stk
103295	G/R 3/4	20.0	33.0 mm	32.0 mm	31,34 € / Stk
103292	G/R 1/4	8.0	18.0 mm	18.0 mm	13,63 € / Stk
103294	G/R 1/2	15.0	27.0 mm	26.0 mm	20,51 € / Stk
103293	G/R 3/8	10.0	21.0 mm	21.0 mm	16,32 € / Stk

More Pictures

