


Datasheet for: 102962


3/2-way solenoid valve brass, NC, 24 V DC, FKM, G 1/8

3/2-way solenoid valve brass, NC, 24 V DC, Sealing material FKM, Medium temperature -10 °C to 100 °C, G 1/8, PN - 15 bar . Directly operated seat valve with spring return and manual operator. Also suitable for vacuum operation.

Type number	107.12
Article number	102962
EAN/barcode	 4047322195775
Your price	45,54 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	58.0 mm
Applications	Compressed air and neutral, non-toxic gases, water, oil
B	33.0 mm
DN	1.2
Electrical connection	Connector socket, can be rotated 180°, PG7 acc. to 43650
Function	Interchangeable magnetic heads (AC/DC)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	60 °C
Max. medium temperature	100 °C
Max. operating pressure	15 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK327
Protection IP	IP 65 (with connector socket fitted)
Sealant	FPM
Thread	G 1/8
Voltage	24 V DC

Variants

Article number	Voltage	Price
102962	24 V DC	45,54 € / Stk
102961	230/50 V AC, 50 Hz	45,54 € / Stk

More Pictures

