


Datasheet for: 102886


2/2-solenoid valve,NC,dir. oper.,230-240V,50-60Hz,G1/8,PN0-10bar

2/2-way solenoid valve brass, NC, dir. operated, 230 - 240V, 50 - 60Hz, 16VA, Medium temp. -10°C to 140°C, FPM, G 1/8, PN 0-10bar . Economy series available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 1314
Article number	102886
EAN/barcode	 4047322158718
Your price	45,55 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	54.0 mm
B	40.0 mm
DN	3.0
Electrical connection	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Function	normally closed (NC)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	80 °C
Max. medium temperature	140 °C
Max. operating pressure	10 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK320
Protection IP	IP 65 (with connector socket fitted)
Sealant	FPM
Thread	G 1/8
Type	2
Valve seat	Brass

Variants

Article number	Thread	Max. operating pressure	Max. ambient temperature	DN	Type	Price
102886	G 1/8	10 bar	80 °C	3.0	2	45,55 € / Stk
102883	G 1/8	18 bar	60 °C	2.3	1	31,34 € / Stk
102884	G 1/8	6 bar	60 °C	2.3	1	31,34 € / Stk
102885	G 1/8	14 bar	80 °C	2.5	2	45,55 € / Stk
102887	G 1/4	14 bar	80 °C	2.5	2	45,55 € / Stk
102888	G 1/4	10 bar	80 °C	3.0	2	45,55 € / Stk
102889	G 1/4	5 bar	80 °C	4.5	2	45,55 € / Stk

More Pictures

