

Datasheet for: 100353


Filter regulator »multifix-mini«, PC container, G 1/4, 0.1-3 bar

Filter regulator »multifix-mini«, PC container and press. gauge, 5 μm , G 1/4, Input pressure max. 16 bar, Control range 0.1-3 bar . Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

Type number C 06-K 3-HA

Article number 100353

EAN/barcode



4047322344715

Your price 42,22 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	40.0 mm
B	165.5 mm
Bowl	Polycarbonate container
C	63.0 mm
Condensate drain	Semi-automatic
D	102.5 mm
DN	5.0
Filter rating	5.0 μm
Flow rate	1450 l/min
Flow rate measurement	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. control range	3.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.1 bar
Page No.	HK067
Pressure gauge display max.	4.0 bar

Pressure gauge
 display min. 0.0 bar
 Sealant NBR
 Series multifix-mini
 Spring bonnet POM-brass
 Thread G 1/4

Variants

Article number	Thread	Min. control range	Max. control range	Flow rate	Price
100353	G 1/4	0.1 bar	3.0 bar	1450 l/min	42,22 € / Stk
100354	G 1/4	0.5 bar	10.0 bar	1450 l/min	42,22 € / Stk
100352	G 1/8	0.5 bar	10.0 bar	1450 l/min	42,22 € / Stk
100351	G 1/8	0.1 bar	3.0 bar	1450 l/min	42,22 € / Stk

More Pictures

