


Datasheet for: 102893



2/2-solenoid valve,NC,dir. operated,24V DC,8W,FKM,G1/4,PN0-9bar

2/2-way solenoid valve brass, NC, directly operated, 24V DC, 8W, Medium temp. -10°C to 140°C, FKM, G 1/4, PN - 9bar . Economy series available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 1325 G
Article number	102893
EAN/barcode	 4047322158831
Your price	45,55 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	54.0 mm
B	40.0 mm
DN	2.5
Electrical connection	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Function	normally closed (NC)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	80 °C
Max. medium temperature	140 °C
Max. operating pressure	9 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK320
Protection IP	IP 65 (with connector socket fitted)
Sealant	FPM
Thread	G 1/4
Type	2
Valve seat	Brass

Variants

Article number	Thread	Max. operating pressure	Max. ambient temperature	DN	Type	Price
102893	G 1/4	9 bar	80 °C	2.5	2	45,55 € / Stk
102890	G 1/8	8 bar	60 °C	2.3	1	31,34 € / Stk
102891	G 1/8	9 bar	80 °C	2.5	2	35,75 € / Stk
102892	G 1/8	6 bar	80 °C	3.0	2	45,55 € / Stk
102894	G 1/4	6 bar	80 °C	3.0	2	45,55 € / Stk
102895	G 1/4	2 bar	80 °C	4.5	2	45,55 € / Stk

More Pictures

