

Datasheet for: 103012


Pressure switch changeover contact design, G 1/4, 0.5 - 2 bar

Pressure switch changeover contact design, galvanised steel, 42 V, Ambient temp. -25 °C to 85 °C, G 1/4, Setting range 0.5 - 2 bar . For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Type number	DS 4034
Article number	103012
EAN/barcode	 4047322126281
Your price	45,66 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjustment range max.	2.0 bar
Adjustment range min.	0.5 bar
Applications	Air, hydraulic oil, oil emulsions, water
Electrical connection	Tab connectors 3 x 6.3 x 0.8
Function	Changeover
Material	Galvanised steel
Max. ambient temperature	85 °C
Min. ambient temperature	-25 °C
Page No.	HK336
Switching frequency	200/min
Switching voltage	42 V
Thread	G 1/4
Type of construction	Spring-loaded diaphragm (NBR)

Variants

Article number	Adjustment range min.	Adjustment range max.	Type of construction	Price
103012	0.5 bar	2.0 bar	Spring-loaded diaphragm (NBR)	45,66 € / Stk
103013	1.0 bar	10.0 bar	Spring-loaded diaphragm (NBR)	45,66 € / Stk
103014	10.0 bar	70.0 bar	Spring-loaded piston	45,66 € / Stk

More Pictures

