


## Datasheet for: 107058


**Pneumatically piloted stop valve, G 1/4, G 1/4 i., G 1/8**

Pneumatically piloted stop valve, G 1/4, G 1/4 i., G 1/8, Working pressure 0.3-10 bar, Temperature max. 60 °C . For stopping and positioning the cylinder movement: If a control signal is present at port 3 (see drawing), air can flow to and from the cylinder. If no control signal is present, the cylinder exhaust air is shut off by the unidirectional valve. The cylinder is stopped. Releasable unidirectional valves are screwed directly onto the cylinder instead of the normal pipe connections. Note: Pilot pressure is depending on operating pressure.

Type number	63.014-14
Article number	107058
EAN/barcode	 4047322107020
Your price	45,66 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

B	43.0 mm
C	25.4 mm
Material	Nickel-plated brass
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Max. operating pressure	10 bar
Max. pilot pressure	2.5 bar
Min. operating pressure	0.3 bar
Min. pilot pressure	0.5 bar
Mounting position	Any, ring piece must be pos. before tightening the valve
Page No.	HK507
Port 1	G 1/4
Port 2	G 1/4
Port 3	G 1/8
Sealant	NBR

## Variants

Article number	Port 1	Port 2	Port 3	Price
107058	G 1/4	G 1/4	G 1/8	45,66 € / Stk
107057	G 1/8	G 1/8	M5	39,37 € / Stk
107059	G 3/8	G 3/8	G 1/8	56,02 € / Stk
107060	G 1/2	G 1/2	G 1/8	86,54 € / Stk

## More Pictures

