

Datasheet for: 103658


3/2-way valve, NAMUR, monostable, NC, G 1/4, 24 V DC

3/2-way valve, NAMUR, NC, Anodised aluminium, Operating temp. max. 70°C, Working pressure 1.5-10 bar, Connection G 1/4, 24 V DC . 3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

| | |
|----------------|--|
| Type number | 551.12 |
| Article number | 103658 |
| EAN/barcode |  4047322272438 |
| Your price | 42,52 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|--|
| Connection | G 1/4 |
| DN | 7.0 |
| Electrical connection | Connector socket Pg 9 |
| Flow rate | 1250 l/min |
| Housing | Aluminium anodised |
| Manual control | latching |
| Max. operating temperature | 70 °C |
| Max. working pressure | 10 bar |
| Medium | Air, neutral gases (filtered) |
| Min. operating temperature | -20 °C |
| Min. working pressure | 1.5 bar |
| Page No. | HK311 |
| Power input | 3 W=/ 5 VA |
| Scope of delivery | Plug connector PG 9, 1 coding pin, 2 Orings, 2 fixing screws |
| Sealant | NBR |
| Spool | Stainless steel |
| Voltage | 24 V DC |

Variants

| Article number | Voltage | Price |
|----------------|--------------|---------------|
| 103658 | 24 V DC | 42,52 € / Stk |
| 103657 | 230 V, 50 Hz | 42,52 € / Stk |

More Pictures

