


Datasheet for: 103661


5/2-way valve, NAMUR, monostable, G 1/4, 230 V, 50Hz

5/2-way valve, NAMUR, Anodised aluminium, Temp. -20 °C to 70 °C, Working pressure 1.5 - 10 bar, Connection G 1/4, 230 V, 50Hz . 3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

Type number	551.31
Article number	103661
EAN/barcode	 4047322272483
Your price	42,52 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
DN	7.0
Electrical connection	Connector socket Pg 9
Flow rate	1250 l/min
Housing	Aluminium anodised
Manual control	latching
Max. operating temperature	70 °C
Max. working pressure	10 bar
Medium	Air, neutral gases (filtered)
Min. operating temperature	-20 °C
Min. working pressure	1.5 bar
Page No.	HK311
Power input	3 W=/ 5 VA
Scope of delivery	Plug connector PG 9, 1 coding pin, 2 Orings, 2 fixing screws
Sealant	NBR
Spool	Stainless steel
Voltage	230 V, 50 Hz

Variants

Article number	Voltage	Price
103661	230 V, 50 Hz	42,52 € / Stk
103662	24 V DC	42,52 € / Stk

More Pictures

